



- / The proven long rail system for trapezoidal sheet applications as well as floating suspension with controlled thermal linear expansion
- / Our most popular system over 3 GW installed worldwide
- / All-rounder with only 4 installation steps also suitable for high loads



Components



SpeedRail

- / Mounting rail with easy insertion mounting into SpeedClips
- / Various lengths available



SpeedClip

- / Mounting brackets for SpeedRail
- / Simple insertion feature
- / Glass fibre reinforced polyamide with EPDM seals
- / Fastened with self-drilling screws for trapezoidal sheet metal



SpeedLock

- / Mounting lock for SpeedRail in case of thermal expansion
- / In a set with MK2 slot nut and stainless steel screw



SpeedConnector

- / Rail connector for SpeedRail
- / Three boreholes for flexible mounting
- / In a set with countersunk screws



AddOn

- / For grid mounting with horizontal modules
- / Seamless module blocks and no second rail layer



RailUp Set

- / Improves rear ventilation of the modules
- / Easier installation of micro inverters

Technische Daten

	SpeedRail / SpeedClip
Scope of application	Trapezoidal sheet roof
Fastening type / roof fixture	Insertion mounting into SpeedClips and screws in the roofing
Requirements	 Sheet thickness: ≥ 0.4 mm steel or ≥ 0.5 mm aluminium Sandwich panel: Approval from manufacturer required Crest width: At least 22 mm Flush area surrounding the bore hole: Ø ≥ 20 mm
Material	 SpeedRail: Aluminium (EN AW-6063 T66; 0.64 kg/m) SpeedClip: Glass fibre reinforced polyamide with EPDM
SpeedRail dimensions W = width [mm] H = height [mm] L = lengths [m]	63 22.5 2.25 / 3.30 / 4.40 / 5.50 m
SpeedClip dimensions	See drawing
Second rail layer	SingleRail or SolidRail

